

CLAIMS

1. A radio-frequency imaging system for noninvasively imaging the internal structure of an object, comprising:

means for generating a beam comprised of radio frequency signals, said signals having a particular wavelength, that is to be passed through said object;

means for transmitting said beam toward said object;

means for receiving said beam after said beam has passed through said object;

scanning means for providing images of said object's internal structure;

means for generating said images of said object's internal structure; and

means for displaying said images of said object's internal structure.

2. The radio-frequency imaging system of claim 1 wherein said radio frequency signals are comprised of a single frequency.

3. The radio-frequency imaging system of claim 1 wherein said radio frequency signals are comprised of multiple frequencies.

Sub  
B5

10074826-021202

Sub  
B5  
4. The radio-frequency imaging system of claim 1 further  
comprising means for generating additional beams and means for  
transmitting additional beams, said means for transmitting said  
additional beams situated proximate said object in order to  
5 obtain localized RF energy cross-beam information.

5. The radio-frequency imaging system of claim 4 wherein  
said additional beams are comprised of radio frequency signals,  
each of a different frequency.

10

6. The radio-frequency imaging system of claim 1 wherein  
said scanning means is physically connected to said beam  
transmitting means and said beam receiving means and moves one  
or both in a linear orientation proximate said object in order  
15 to measure said beam's attenuation and to create an X-Y planar  
scan of said object representing a spatial position of said  
beam through said object.

7. The radio-frequency imaging system of claim 1 wherein  
20 said scanning means is physically connected to said beam  
transmitting means and beam receiving means and moves one or  
both in a rotational orientation about said object, and moves  
one or both along said object, in order to measure said beam's  
attenuation as a function of axial position and azimuth angle  
25 and to create a three-dimensional cylindrical tomographical

202509284267

Sub  
B5  
scan of said object representing attenuation of the beam as a function of a spatial position of said beam through said object.

5        8.    The radio-frequency imaging system of claim 1 wherein said signal transmitting means is a parabolic reflector antenna.

10       9.    The radio-frequency imaging system of claim 1 wherein said signal transmitting means is a cassegrain antenna.

10       10.   The radio-frequency imaging system of claim 1 wherein said signal transmitting means is a horn antenna.

15       11.   The radio-frequency imaging system of claim 1 wherein said signal transmitting means is a waveguide having a small aperture.

20       12.   The radio-frequency imaging system of claim 1 wherein said beam has a width greater than the wavelength of said radio frequency signals.

13.    The radio-frequency imaging system of claim 1 wherein said signal beam is comprised of spherical wavefronts.

10074826-021202

Sub  
B5

14. The radio-frequency imaging system of claim 1 wherein said beam receiving means are situated within said beam's path, said beam receiving means for measuring a ratio of received signal power to transmitted signal power.

5

15. The radio-frequency imaging system of claim 5 wherein said beam receiving means are situated within said beam's path, said beam receiving means for measuring a ratio of received signal power to transmitted signal power.

10

16. The radio-frequency imaging system of claim 1 further comprising one or more auxiliary detectors coupled to said beam transmitting means and said beam receiving means, said auxiliary detectors situated at predetermined angles in relation to the path of said beam in order to gather additional information regarding RF energy scattered out of said beam.

15

17. The radio-frequency imaging system of claim 5 further comprising one or more auxiliary detectors coupled to said beam transmitting means and said beam receiving means, said auxiliary detectors situated at predetermined angles in relation to the path of said beams in order to gather additional information about RF energy scattered out of said beams.

20

25

10074825-021202

18. The radio-frequency imaging system of claim 17 wherein said one or more auxiliary detectors are sensitive to a frequency caused by interaction of said beams with the internal structure or organs of said object.

5

19. The radio-frequency imaging system of claim 18 wherein said object is a live human or animal and said interaction of said beams produces a therapeutic effect.

10

20. The radio-frequency imaging system of claim 14 wherein said beam receiving means further comprises an effective detector aperture less than or equal to one wavelength of the transmitted and received radio frequency signals.

15

21. A security imaging system for noninvasively scanning people or objects comprising:

means for generating a beam comprised of radio frequency signals, said signals having a particular wavelength, that is to be passed through said person or said object;

means for transmitting said beam toward said person or said object;

means for receiving said beam after said beam has passed through said person or said object;

Sub  
B5

10074826 "021202

Sub B5  
1007-826-021202  
scanning means for providing images of said person or said object's internal structure;

means for generating said images of said person or said object's internal structure; and

5 means for displaying said images of said person or said object's internal structure.

22. A method of noninvasively imaging the internal structure of an object, person or animal, said method  
10 comprising the steps of:

generating a beam comprised of radio frequency signals that is to be passed through said object;

transmitting said beam toward said object;

receiving said beam after said beam has passed through  
15 said object;

scanning said beam for providing images of said object's internal structure;

generating said images of said object's internal structure; and

20 displaying said images of said object's internal structure.

23. The method of claim 22 wherein said radio frequency signals are comprised of a single frequency.

Sub  
B5

24. The method of claim 22 wherein said radio frequency signals are comprised of multiple frequencies.

25. The method of claim 22 further comprising the steps  
5 of generating additional beams and transmitting said additional beams, said step of transmitting said additional beams to obtain localized RF energy cross-beam information.

26. The method of claim 25 wherein said additional beams  
10 are comprised of radio frequency signals, each of a different frequency.

27. The method of claim 22 wherein said step of scanning  
said beam further comprises the steps of measuring said beam's  
15 attenuation and creating an X-Y planar or planar tomographic scan of said object representing a spatial position of said beam through said object.

28. The method of claim 22 wherein said step of scanning  
20 said beam further comprises the steps of measuring said beam's attenuation to create an attenuation map, creating a three-dimensional cylindrical tomographical scan of said object representing a spatial position of said beam through said object, and processing the attenuation map to yield an image of  
25 internal organs or structures of the object.

2025-09-23 09:20:00

Sub  
B5

29. The method of claim 22 further comprising the step of measuring a ratio of received signal power to transmitted signal power, said step of measuring performed by said beam  
5 receiving means situated within the path of said beam.

10074826-021202

30. The method of claim 26 further comprising the step of measuring a ratio of received signal power to transmitted signal power, said step of measuring performed by said beam  
10 receiving means situated within the path of said beam.

31. The method of claim 22 further comprising the step of gathering additional information regarding RF energy scattered out of said beam via one or more auxiliary detectors situated  
15 at predetermined angles in relation to the path of said beam.

32. The method of claim 26 further comprising the step of gathering additional information about RF energy scattered out of said beams via one or more auxiliary detectors situated at  
20 predetermined angles in relation to the path of said beams.

33. The method of claim 32 wherein said one or more auxiliary detectors are sensitive to a frequency caused by interaction of said beams with the internal structure or organs  
25 of said object.



Sub  
B5

34. The method of claim 33 wherein said object is a live human or animal and said interaction of said beams produces a therapeutic effect.

5

35. The method of claim 29 further comprising the step of providing a detector with an effective aperture less than or equal to one wavelength of the transmitted and received radio frequency signals.

10

36. A system for noninvasively affecting, processing or interacting with internal structures, subsystems and/or components of an industrial object or system comprising:

means for transmitting one or more scanned beams of radio frequency energy wherein each said beam has a different frequency, through the object or the system such that the radio frequency energies are delivered to a volume of intersection of said beams, and wherein combinations of said frequencies interact specifically with said internal structures, said subsystems and/or said components to create a desired effect.

15

20

37. The imaging system of claim 1 further comprising computer means for comparing said generated images of said object with actual images of said object, said actual images of said object stored in a computer storage medium, said means for

25

2025-02-20 09:48:26

Sub  
B5

comparing to determine if said object is missing components,  
and if said object is a human or animal, to determine if said  
object is missing an internal organ or has broken or damaged an  
internal organ, said computer means capable of correcting said  
5 generated image to more closely match said stored actual image.

202720 922420

38. The method of claim 22 further comprising the step of  
comparing said generated images of said object with actual  
images of said object, said actual images of said object stored  
10 in a computer storage medium, said step of comparing to  
determine if said object is missing components, and if said  
object is a human or animal, determining if said object is  
missing an internal organ or has broken an internal organ, said  
computer means capable of correcting said generated image to  
15 more closely match said stored actual image.

39. The imaging system of claim 37 further comprising  
software instructions stored in said computer storage medium,  
said software instructions to compensate for diffraction  
20 effects from the object.

---